



Compact Palletizer™

Optipall Compact is an automatically operated palletizing system for various types of carton/block pallets which are then transported to the cargo lift or to front cargo hold.

The palletizer unit is automatically operated based on block size 530x530x100 mm /1070x475x-100mm (to be agreed) and fillet cartons with size 485x255x200 mm (different dimensions are available).

Size of pallet (footprint), between 800 -1200 mm (to be agreed). Adjustable numbers of cartons on each pallet.

Automatically operated plastic wrapper. Automatic block lift to lift block to top of pallet for stacking.

Block security device installed on top of palletizer. Automatic lift for pallet to top of palletizer. Palletizer with integrated plastic wrapper. Amount of plastic wrap to be applied is adjustable.

Fully automatic plastic wrapping including termination of plastic after wrapping and attaching of plastic for new pallet.

Block infeed height: flexible (to be agreed). Pallet conveyor outfeed height: 300-350mm.

Made of painted steel (optionally stainless steel).

Empty pallet is automatically transported to pallet stand with use of roller conveyor.

SPECIFICATIONS:

- Material Stainless steel AISI 304.
- Electrical and pneumatical operation.
- PLC control system.
- Foundation to deck.
- Security fence.
- Service stand on 2 sides.
- Net height = pallet stack + 1000 mm.