



Compact Palletizer

- A unique palletizing system.



Optipall compact is a automatic operated palletizing system for a various type of cartons/block transporting pallets to cargo lift or to front cargo hold.

The palletizer unit is automatic operated based on block size 530x530x100 mm /1070x475x100mm (to be agreed) and fillets cartons with size 485x255x200 mm (different dimensions are available).

Size of pallet (footprint), between 800 -1200 mm (to be agreed). Adjustable numbers of cartons on each pallet.

Automatic operated plastic wrapper. Automatic block lift for blocks to top of palletizer.

Block security device installed on top of palletizer. Automatic lift for pallet to top of palletizer. Palletizer with integrated plastic wrapper, adjustable numbers of plastic wrapping.

Fully automatic plastic wrapping including cutting of plastic after wrapping and attaching of plastic for new pallet.

Block infeed height: flexible (to be agreed).
Pallet conveyor outfeed height: 300-350mm.

Made of painted steel (optionally stainless steel).

Empty pallets is automatically transported in to pallet stand with use of roller conveyor.

SPECIFICATIONS:

- Material Stainless steel AISI 304.
- Electrical and pneumatical operated.
- PLC control system.
- Foundation to deck.
- Security fence.
- Service stand on 2 sides.
- Net height = pallet stack + 1000 mm.