



GSPG 35/75/100 ENSILAGE

Ensilage unit with integrated grinder and circulation pump is an effective solution for making ensilage in the fishing industry.

Ensilage unit with integrated grinder and circulation pump is an effective solution for making ensilage in the fishing industry. The oval shape of the tank makes an optimal circulation in the ensilage with no dead points that can cause problems.

GSPG has a powerful grinder pump to grind, circulate and unload the tank. The system includes an automatic dosage pump for formic acid. The dosage pump secures the right Ph level in the tank, and is a secure way of handling the acid for the operators.

The inlet is as low as possible to make the loading easy, and the hatch is large to prevent spill when filling the fish into the tank. The tank is easily filled with 1000l standard bins. The outlet is equipped with a 4" valve.

SPECIFICATIONS

Material	Stainless steel aisi 304/316
Outlet flange	4''
Acid dosing	Standard dosage pump
Control cabinet	Stette software
Standard equipment	Fork lift pockets/lifting lugs



MODELS

MODEL	PUMP	POWER	GRINDER	VOLTAGE	VOLUME	ACID DOSAGE PUMP	FUSE
GSPG 35	FS312	12	GS150-500	3X230/400V	3500	YES	45/32 AMP
GSPG 75	GS312	12	GS150-500	3X230/400V	7500	YES	45/32 AMP
GSPG 100	FS312	12	GS150-500	3X230/400V	10000	YES	45/32 AMP