





SPECIFICATIONS

Material	Stainless steel aisi 304/316
Outlet flange	DN75
Acid dosing	Standar dosage pump
Control cabinet	Stette software
Standard equipment	Fork lift pockets/lifting lugs

MOBILE GRINDER

With a grinding capacity of up to 12 tons pr hour, combined with automatic acid dosing and a powerful pump for delivery directly to the ensilage tank, this is an unit that has great advantages in the fishing industry.

Type GS150 TF2P

GS150-TF2P can handle the daily tasks in dead fish handling as well as being a emergency system. With a grinding capacity of up to 12 tons pr hour, combined with automatic acid dosing and a powerful pump for delivery directly to the ensilage tank, this is an unit that has great advantages in the fishing industry.

The model GS150 TF2P will be delivered as a complete unit with 1000l Funnel with lid, Grinder GS150(300–600), Control system, Acid dozing (option) and Pump. The pump capacity matches the grinder and can pump the grinded substance directly to the ensilage tank. The choice of materials used in the production of the grinder ensures long lifetime and little maintenance.

MODELS

MODEL	POWER	VOLTAGE	CAPACITY	FUNNEL	WEIGHT	LENGTH	WIDTH	HEIGHT
GS150-300-TF2P	10	3X240/400	3000	1000	750	1980	1694	1504
GS150-500-TF2P	12	3X240/400	6000	1000	800	1980	1694	1504
GS150-600-TF2P	12	3X240/400	12000	1000	900	1980	1694	1504