



SPECIFICATIONS

Size	To be adapted to the horizontal freezers
Plate size	1250, 1550, 1750, 1950, 2150, and 2350
Materials	Stainless steel profiles
Plates	Extruded aluminium, welded waterproof
Hydr. cylinders:	Seawater resistant brass, SS rod/piston
Hydr. motor/gear	Metallized steel
Oil pressure	Min. 100 bar
Wire	12mm Stainless steel
Valves	Metallized steel / Stainless steel

PRE-PRESSING STATION

Simplify the transport of blockframes/catering trays from the packingtable to the horizontal freezers

- Simplify the transport of blockframes/catering trays from the packingtable to the horizontal freezers
- The frames are easily pushed into the horizontal freezer
- Accumulates frames, equal to 1 freezer
- Pre-pressing of fishblock before freezing
- Reduces the unloading/loading time to 10 min. per freezer
- Increases productivity, 11 cycles per freezer per day
- 2 units cover 4 horizontal platefreezers. Each unit can service
- 3 freezers. It can be pulled on rails, by means of a hydraulic winch

Additional products from Optimar, to make a system is Packing table, Lifting table, Blockjector and Auto ejecting system.

The unit is opened/pressed with hydraulic cylinders/control valves. The pressure is regulated with pressure regulating valve. Hydr. winch can be operated by separate control valve.

